

Kaye ValProbe RT 5-Channel Datalogger with Bendable Sensors

MAXIMIZED EFFICIENCY WITH 5-CHANNEL TECHNOLOGY AND BENDABLE SENSORS



The real-time Kaye ValProbe RT data loggers, obtainable in one and two sensor versions, are now also available with five sensors in conjunction with bendable probes.

The advanced electronics of the loggers, in combination with the PT-1000 Sensors, achieve an accuracy of up to 0.10°C, while also facilitating extended battery life. This logger supports up to 100,000 samples per measurement channel, thus allowing for a total of up to half a million data points per device.

Retaining the proven dual antenna technology already used throughout the Kaye ValProbe RT series ensures seamless data transfer. This applies even under difficult measuring

conditions, such as in a closed stainless-steel container. This newly developed 5-channel real-time data logger can be used for all applications from 0°C to 400°C. Combined with an equally optimized insulating canister that uses vacuum technology, it can also be used for applications over 140°C. This establishes it as the ideal data logger for usage in hot air tunnels, catering to those who prefer not to compromise on real-time data, even in such applications. Thus, the time-consuming and admittedly cumbersome installation and updating of, for example, thermocouples as measurement sensors is eliminated. The expansion to 5 measurement channels per logger also reduces the introduction of disturbing mass into the sterilization tunnel by the measuring equipment itself. This has the additional

side effect of significant cost savings, as fewer data loggers and canisters are needed. Of course, this is accomplished without compromising the accuracy of measurements. The additionally reduced sensor diameter of the flexible sensor of only 1.6mm (0.063") offers a balanced mix of flexibility and stability. This ensures optimal insertion and secure positioning of the sensor tip even in small vials.

TECHNICAL SPECIFICATIONS

- 5-Channel Data Logger
- 100,000 records per channel
- Temperature range: 0 – 400°C
- Measurement accuracy:
 - 0-140°C: 0.1°C
 - 140-400°C: 0.25°C
- Cable Diameter: 1.6mm (0.063")
- Probe tip Diameter: 2.0mm (0.078")
- Standard probe length: 61cm (24")
- Supported from Kaye ValProbe RT Software version 1.2 and onwards

APPLICATIONS

In addition to the previously mentioned application in hot air tunnels, the wide temperature range combined with

5 measurement channels per data logger enables cost-optimized applications in other areas. The properties already mentioned, such as introducing less disturbing mass in connection with the 5-channel technology are also advantageous in the qualification of hot air cabinets or high temperature ovens.

The qualification of CO₂ incubator sterilization at 180°C also benefits from these qualities, cost optimization through a reduced number of necessary data loggers and the secure transmission of measured real-time data. The application in the area of cleaning unit qualification (Washer Disinfectors) is also possible, as is its use in a small sterilizer.

- Sterilization Tunnels
- Hot air cabinets/ High-temperature ovens
- CO₂ Incubators
- Water-Cascade Autoclaves
- Steam Sterilizer
- Cleaning and Disinfection equipment
- Fermenters
- Drying Ovens
- Climate Chambers



Kaye representative contact:

Request a demo:

EUROPE, MIDDLE EAST, AFRICA AND ASIA

Amphenol Advanced Sensors Germany GmbH
Sinsheimer Strasse 6
D-75179 Pforzheim
T: +49 (0) 7231-14 335 0
F: +49 (0) 7231-14335 29
Email: kaye@amphenol-sensors.com

USA/AMERICAS

Amphenol Thermometrics, Inc.
967 Windfall Road
St. Marys, PA 15857
T: +1(814) 834-9140
F: +1(814) 781-7969
Email: kaye-us@amphenol-sensors.com

INDIA

Amphenol Interconnect India Pvt Ltd.
Plot no. 6, Survey No.64 | Software Units layout
MAHAVEER TECHNO PARK
HITECH CITY, MADHAPUR | Hyderabad,
Telangana – 500081 | T: +91 40 33147100
Email: kaye-india@amphenol-sensors.com

CHINA

Amphenol (Changzhou) Connector
Systems Co., Ltd, Building 10,
Jintong Industrial Park, No. 8 Xihu Road,
Wujin High-Tech Development Zone,
Changzhou, Jiangsu 213164
T: 0086-519-83055197



Warranty and disclaimer: The information mentioned on documents are based on our current tests, knowledge and experience. Because of the effect of possible influences in an application of the product, they do not exempt the user from their own tests, checks and trials. A guarantee of certain properties or a guarantee for the proper suitability of the product for a specific, especially permanent application can not be derived from our data. Liability is therefore excluded to that extent permitted by law. Any proprietary rights of third parties as well as existing laws and regulations must be observed by the recipient of the product on his own responsibility.

© 2024 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice. Other company names and product names used in this document are the registered trademarks or trademarks of their respective owners.